CDF UTILITY SUPPLY

CDF-T2 TURRET TRAILER

PRODUCT INFORMATION

CDFUtilitySupply.ca

CDF-T2 TURRET TRAILER

GENERAL SPECIFICATIONS

- **Ease of Use**
- **Low Maintenance**
- **Durable**

GVWR	16,450 lbs.
REEL DIAMETER	72"
REEL WIDTH*	54"
OVERALL WIDTH	96"
REEL WEIGHT**	2 X 5,000 lbs.
OVERALL LENGTH	223" (approximate)
TIRES	(2) 235/80R 16 (E range)
WHEELS	(2) 16 x 6 on .19 Offset
BRAKES	12" x 2" Electric w/Safety Breakaway Kit
AXLE	Tandem Dexter 7,000lbs EZ Lube leaf-spring - Optional Air Brakes
REEL SHAFT DIA.	2.5" OD with Centering Cones
HITCH	3" ID 4-Bolt Draw bar - Grade 8 Fasteners
ELECTRICAL PLUG	Customer choice
SAFETY CHAINS	(2) l /2" Zinc Plated Grade 70 Alloy
TONGUE JACK	10k Spring Return Side Wind Drop Leg Jack
STABILIZING JACKS	(2) 7K Top-wind drop leg jacks
MUDFLAPS	1/2" thick, fender mounted 7" above ground
TRAILER FRAME	6" x 4" x 1/4" Steel Tubing
CENTER TONGUE	6" x 3" x 1/4" Steel Tubing

TURRETS	110,000 Axial and 20,000 Moment load sealed thrust bearings lockable at 6 degree intervals. Self-supporting, removable A-frames to turn trailer into flatbed if needed. Spring loaded handle lock
D-LUGS	(4) Tie-down Lugs for cargo containment
SADDLES	Patent Pending Autolock feature allows for hands-free, instant engage loading. Saddle surface is high impact Bronze.
FENDERS	1/8" diamond plate welded to catwalk
CATWALK	16" wide Catwalk w/Heavy Duty tread-plate
LIGHTS & ELEC'L	FMVSS108 DOT Approved Sealed Rubber Grommet Mounted LED Lighting.
CONSPICUITY	Unit taped w/ 2"DOT-C2 reflective tape (High Quality)
GROUNDING LUG	5/8" x 5" bronze lug bolted to frame
FASTENERS	All Grade 8 (Except on Aluminum)
FINISH	Shot-blasted, zinc-rich primer & Powder-Coated, Upgrade to Galvanized Available
WHEEL CHOCK HOLDERS	l2ga steel plate

* Without spacers ** Approximate without options

P (905) 396-5964
E info@cdfutilitysupply.ca

For more info contact your **CDF** Sales Rep
CDFUtilitySupply.ca